

- A:** \_\_\_\_\_ Center line length from top pin at ball socket to top pin hole of bottom clevis. Measure your stationary side link, usually on the left side of the tractor
- Or--**
- A1:** Collapsed \_\_\_\_\_ Expanded \_\_\_\_\_ If both of your side links are adjustable, the collapsed length and the maximum extended working length (two measurements needed)
- B:** \_\_\_\_\_ Center line length from top pin at ball socket to top of side link shaft
- C:** \_\_\_\_\_ Outside diameter of ball socket housing
- D:** \_\_\_\_\_ Ball socket pin diameter
- E:** \_\_\_\_\_ Ball socket width
- F:** \_\_\_\_\_ Amount of degrees of the top ball socket from the side link shaft; is the pin 90° to the side link shaft or something else?
- G:** \_\_\_\_\_ Inside total depth of bottom clevis
- H:** \_\_\_\_\_ Center line distance of top clevis pin hole of bottom clevis to inside top of bottom clevis
- I:** \_\_\_\_\_ Center line distance of second bottom clevis hole from top hole of bottom clevis
- J:** \_\_\_\_\_ Center line distance of third bottom clevis hole from second hole (should be same as I)
- K:** \_\_\_\_\_ Slot for floating link clevis, contact us if your side link has this
- L:** \_\_\_\_\_ Pin diameter size for lower clevis
- M:** \_\_\_\_\_ Clevis width
- N:** \_\_\_\_\_ Clevis width inside
- O:** \_\_\_\_\_ Clevis width outside
- P:** \_\_\_\_\_ Degrees of bottom clevis to the side link shaft. A straight clevis would have the clevis pin 90° to the side link shaft. How many degrees is your clevis pin to the side link shaft?

